

	Standard Features	Standard Options	Customizing / Special / Optional
<p>Glazing Options</p>	<ul style="list-style-type: none"> • Premium quality flat glass complying with ASTM C1036. • 3/4" (19mm) maximum glass thickness. • Operating Units: Glazed with closed-cell foam glazing tape and/or silicone sealant and removable interior vinyl glazing bead. • Picture/Transom Units: Glazed with closed-cell foam glazing tape and/or silicone sealant and removable interior vinyl glazing bead. • Factory glazed fabrication complies with requirement of Section 08810 and with AAMA/WDMA 101/I.S.2/NAFS • Safety glass tempered products complying with testing requirements in 16 CFR 1201, for Category II materials. 	<p>Standard Insul Options:</p> <ul style="list-style-type: none"> • Low-E (standard) • Clear • Super SunBlocker Low-E • Super SunBlocker w/IS 15 • Low-E 366 • 180 Low-E (Passive Solar) <p>Ultra-R (3/4"), Single Film Options:</p> <ul style="list-style-type: none"> • Argon • Krypton <ul style="list-style-type: none"> • All insul glass above with Argon UNLESS specified or capillary tubes necessary for high altitudes. <p>Tempered:</p> <ul style="list-style-type: none"> • Both Lites • 1 Lite, Interior • 1 Lite, Exterior <p>Glass Spacer Channel for Standard 3/4" Insul options:</p> <ul style="list-style-type: none"> • Standard (Technospacer Tin Plate) • Stainless Steel Intercept Spacer • Technoform Spacer • Dark Bronze Anodized • Light Bronze Anodized • Please note that not all spacer options are available with all glass types. <p>Glass Spacer for Ultra R:</p> <ul style="list-style-type: none"> • Standard • Black 	<p>Tints:</p> <ul style="list-style-type: none"> • Bronze Tint • Grey Tint • Green <p>Obscure Glass:</p> <ul style="list-style-type: none"> • Obscure - Standard
<p>Hardware</p>	<ul style="list-style-type: none"> • Concealed sliding nylon shoe hinges applied directly to sash. • Stainless steel hinge track located for maximum sash support. • Encore folding handle, White or Beige. • Handle covers, White or Beige. • Scissor Arm Operators. • Limit Device available upon request. • 10" (254mm) egress hinge arm. • 10" (254mm) hinge track. 	<p>Coastal Corrosion:</p> <ul style="list-style-type: none"> • Truth Encore, E-Gard 300 series. Level II SST <i>optional</i> stainless steel dual arm operator. • Truth Encore, E-Gard 300 series Level II SST <i>optional</i> stainless steel corrosion-resistant gear operator provides smooth operation. 	
<p>Weatherstrip</p>	<ul style="list-style-type: none"> • Units are provided with bulb weatherstripping designed for a tight seal when sash are closed. <p>Weatherstripping system include: On Sash:</p> <ul style="list-style-type: none"> • Bulb with fin weatherstrip applied to top rail, bottom rail and jambs. 	<p>Color: White. Beige.</p>	
<p>Insect Screen</p>	<ul style="list-style-type: none"> • Removable flange style insect screens provided for operating units, fitted to the interior of the window. • Plunger design, 2 on each side of screen. • Screen fabric is 18 x 16 fiberglass mesh. • Screen frame is roll-form tubular aluminum 0.019" (.483mm) with vinyl corner 	<p>Screen frame color:</p> <ul style="list-style-type: none"> • White • Beige <p>Screen shipped:</p> <ul style="list-style-type: none"> • Applied • Separately. 	

	Standard Features	Standard Options	Customizing / Special / Optional
<p>Grille Options</p>	<ul style="list-style-type: none"> • Simulated Divided Lite (SDL) Exterior and interior aluminum bars adhered to glass with double-coated acrylic foam tape. With or without aluminum internal spacer bar. • Grilles in Airspace (GIAS) 	<p>Specify Grille Style →</p> <p>Specify Exterior Grille Color:</p> <ul style="list-style-type: none"> • Match Exterior Color (standard) • White • Eggshell • Colonial White • Burnt Sun • Dried Wheat • Sand • Patina Green • Aspen Moss • Bronze • Green • Sage Brown • Bahama Brown • Brick Red • Boysenberry • Jet Black <p>Grille Pattern (Configuration):</p> <ul style="list-style-type: none"> • Colonial • Queen Anne • Ladder • Craftsman 	<p>SDL'S (with or without aluminum internal spacer)</p> <ul style="list-style-type: none"> • 7/8" (22mm) Traditional profile (Ext/Int) • 2" (51mm) Traditional profile (Ext/Int) <ul style="list-style-type: none"> • Aluminum internal glass spacer: <ul style="list-style-type: none"> - Standard - Dark Bronze Anodized - Light Bronze Anodized • GIAS (Grille In Airspace) <ul style="list-style-type: none"> • Flat (profile), 5/8" x 3/16" (16mm x 5mm) • Contour (profile), 11/16" x 5/16" (18mm x 8mm) <p>Grille Pattern: Special upon request.</p>
<p>Options</p>	<ul style="list-style-type: none"> • NFRC rated. • Thermal values available on www.supersealwindows.com. • DP labels applied upon request. 		
<p>Additional Glass Specifications</p>	<ul style="list-style-type: none"> • Low-E (standard): dual insulated glass consisting of one lite of multi-layered 7138 Low-E coatings sputter coated on the #2 surface and one lite of clear glass. Argon filled. • Clear: dual insulated glass consisting of two lites of clear glass. • Ultra-R, Single Film: dual insulated glass consisting of one lite of multi-layered 7138 Low-E coatings sputter coated on the #2 surface, .030 Heat Mirror film and one lite of clear glass. • Super Sun Blocker Low-E: dual insulated glass consisting of one lite of multi-layered 6227 Low-E coatings sputter coated on the #2 surface and one lite of clear glass. • Super Sun Blocker with IS15 Low-E: dual insulated glass consisting of one lite of multi-layered 6227 Low-E coatings sputter coated on the #2 surface and one lite of IS15 Low-E coating on #4 surface. • Low-E 366: dual insulated glass consisting of one lite of multi-layered 366 Low-E coatings sputter coated on the #2 surface and one lite of clear glass. • Low-E 180 Passive Solar: dual insulated glass consisting of one lite of multi-layered 180 Low-E coatings sputter coated on the #3 surface and one lite clear glass. 		
<p>Warranty</p>	<p>Warranty Period, First Purchaser</p> <ol style="list-style-type: none"> 1 (one) Year Limited Warranty: Glass Stress Cracks Lifetime Limited Warranty: Parts and Screens Specialty Glass: 5 (five)-year limited warranty. Exterior paint: 10 (ten)-year limited warranty. Dual Insulated Glass: 20 (twenty)-year limited warranty 		
<p>Manufacturer</p>	<p>Superseal Windows & Doors; 1815 Water Street, Merrill, WI 54452. Toll Free Tel: 800-433-4873. Web: http://www.supersealwindows.com.</p>		