

| Page 2 of 3 | Standard Features | Standard Options | Customizing / Special / Optional |
|-------------------------------|---|--|--|
| <p>Glazing Options</p> | <ul style="list-style-type: none"> • Premium quality flat glass complying with ASTM C1036. • 3/4" (19mm) maximum glass thickness. • Operating Units: Glazed with closed-cell foam glazing tape and/or silicone sealant and removable interior vinyl glazing bead. • Picture/Transom Units: Glazed with closed-cell foam glazing tape and/or silicone sealant and removable interior vinyl glazing bead. • Factory glazed fabrication complies with requirement of Section 08810 and with AAMA/WDMA 101/I.S.2/NAFS • Safety glass tempered products complying with testing requirements in 16 CFR 1201, for Category II materials. | <ul style="list-style-type: none"> • Low-E (standard) • Clear • Super SunBlocker Low-E • Super SunBlocker w/IS 15 • Low-E 366 • 180 Low-E (Passive Solar) • Ultra-R (3/4"), Single Film <ul style="list-style-type: none"> • Argon • Krypton • All insul glass above with Argon UNLESS specified or capillary tubes necessary for high altitudes. <p>Tempered:</p> <ul style="list-style-type: none"> • Both Lites • 1 Lite, Interior • 1 Lite, Exterior <p>Glass Spacer Channel for Standard 3/4" Insul options:</p> <ul style="list-style-type: none"> • Standard (Technospacer Tin Plate) • Stainless Steel Intercept Spacer • Technoform Spacer • Dark Bronze Anodized • Light Bronze Anodized <p>Please note that not all spacer options are available with all glass types.</p> <p>Glass Spacer for Ultra R:</p> <ul style="list-style-type: none"> • Standard • Black | <p>Tints:</p> <ul style="list-style-type: none"> • Bronze Tint • Grey Tint • Green <p>Obscure Glass:</p> <ul style="list-style-type: none"> • Obscure - Standard |
| <p>Hardware</p> | <ul style="list-style-type: none"> • Concealed sliding nylon shoe hinges applied directly to sash. • Stainless steel hinge track located for maximum sash support. • Guide bar operable system. • Roto folding handle, White or Beige. • Roto Split and Dual Arm Operators, White or Beige. • Optional Limit Device available. • Tie bars. | <p>Coastal Corrosion stainless steel hardware:</p> <ul style="list-style-type: none"> • Dual arm operator and gear operator provides smooth operation. <p>Hinge Arms</p> <ul style="list-style-type: none"> • 14" Standard • 10" Egress <ul style="list-style-type: none"> • E-gard • Stainless Steel | |
| <p>Weatherstrip</p> | <ul style="list-style-type: none"> • Units are provided with bulb weatherstripping designed for a tight seal when sash are closed. <p>Weatherstripping system include:</p> <p>On Sash:</p> <ul style="list-style-type: none"> • Bulb with fin weatherstrip applied to top rail, bottom rail and jambs. | <p>Color:</p> <p>White. Beige.</p> | |
| <p>Insect Screen</p> | <ul style="list-style-type: none"> • Removable flange style insect screens provided for operating units, fitted to the interior of the window. • Plunger design, 2 on each side of screen. • Screen fabric is 18 x 16 fiberglass mesh. • Screen frame is roll-form tubular aluminum 0.019" (.483mm) with vinyl corner keys. | <p>Screen frame color:</p> <ul style="list-style-type: none"> • White • Beige <p>Screen shipped:</p> <ul style="list-style-type: none"> • Applied • Separately. | |

| | Standard Features | Standard Options | Customizing / Special / Optional |
|---|---|---|---|
| <p>Grille Options</p> | <ul style="list-style-type: none"> • Simulated Divided Lite (SDL) Exterior and interior aluminum bars adhered to glass with double-coated acrylic foam tape. With or without aluminum internal spacer bar. • Grilles in Airspace (GIAS) | <p><u>Specify Grille Style</u> →</p> <p><u>Specify Exterior Grille Color:</u></p> <ul style="list-style-type: none"> • Match Exterior Color (standard) • White • Eggshell • Colonial White • Burnt Sun • Dried Wheat • Sand • Patina Green • Aspen Moss • Bronze • Green • Sage Brown • Bahama Brown • Brick Red • Boysenberry • Jet Black <p>Grille Pattern (Configuration):</p> <ul style="list-style-type: none"> • Colonial • Queen Anne • Ladder • Craftsman | <p>SDL'S (with or without aluminum internal spacer)</p> <ul style="list-style-type: none"> • 7/8" (22mm) Traditional profile (Ext/Int) • 2" (51mm) Traditional profile (Ext/Int) • Aluminum internal spacer: <ul style="list-style-type: none"> - Standard - Dark Bronze Anodized - Light Bronze Anodized <p>• GIAS (Grille In Airspace)</p> <ul style="list-style-type: none"> • Flat (profile), 5/8" x 3/16" (16mm x 5mm) • Contour (profile), 11/16" x 5/16" (18mm x 8mm) <p>Grille Pattern: Special upon request.</p> |
| <p>Options</p> | <ul style="list-style-type: none"> • NFRC rated. • Thermal values available on www.supersealwindows.com. • DP labels applied upon request. | | |
| <p>Additional Glass Specifications</p> | <ul style="list-style-type: none"> • Low-E (standard): dual insulated glass consisting of one lite of multi-layered 7138 Low-E coatings sputter coated on the #2 surface and one lite of clear glass. Argon filled. • Clear: dual insulated glass consisting of two lites of clear glass. • Ultra-R, Single Film: dual insulated glass consisting of one lite of multi-layered 7138 Low-E coatings sputter coated on the #2 surface, .030 Heat Mirror film and one lite of clear glass. • Super Sun Blocker Low-E: dual insulated glass consisting of one lite of multi-layered 6227 Low-E coatings sputter coated on the #2 surface and one lite of clear glass. • Super Sun Blocker with IS15 Low-E: dual insulated glass consisting of one lite of multi-layered 6227 Low-E coatings sputter coated on the #2 surface and one lite of IS15 Low-E coating on #4 surface. • Low-E 366: dual insulated glass consisting of one lite of multi-layered 366 Low-E coatings sputter coated on the #2 surface and one lite of clear glass. • Low-E 180 Passive Solar: dual insulated glass consisting of one lite of multi-layered 180 Low-E coatings sputter coated on the #3 surface and one lite clear glass. | | |
| <p>Warranty</p> | <p>Warranty Period, First Purchaser</p> <ol style="list-style-type: none"> 1 (one) Year Limited Warranty: Glass Stress Cracks Lifetime Limited Warranty: Parts and Screens Specialty Glass: 5 (five)-year limited warranty. Exterior paint: 10 (ten)-year limited warranty. Dual Insulated Glass: 20 (twenty)-year limited warranty | | |
| <p>Manufacturer</p> | <p>Superseal Windows & Doors; 1815 Water Street, Merrill, WI 54452. Toll Free Tel: 800-433-4873. Web: http://www.supersealwindows.com.</p> | | |