



	Standard Features	Standard Options	Customizing / Special / Optional
<p><b>Glazing Options</b></p>	<ul style="list-style-type: none"> <li>• Premium quality flat glass complying with ASTM C1036.</li> <li>• 3/4" (19mm) glass thickness.</li> <li>• 1" (25mm) glass thickness.</li> <li>• <b>Operating Units:</b> Glazed with closed-cell foam glazing tape and/or silicone sealant and removable interior vinyl glazing bead on top fixed glass and .exterior vinyl glazing bead on operating sash.</li> <li>• <b>Picture/Transom Units:</b> Glazed with closed-cell foam glazing tape and/or silicone sealant and removable interior vinyl glazing bead.</li> <li>• Factory glazed fabrication complies with requirement of Section 08810 and with AAMA/WDMA 101/I.S.2/NAFS</li> <li>• Safety glass laminated and tempered products complying with testing requirements in 16 CFR 1201, for Category II materials.</li> </ul>	<ul style="list-style-type: none"> <li>• Low-E (standard)</li> <li>• Clear</li> <li>• 1/4" Laminated</li> <li>• 1/4" Laminated Low-E</li> <li>• Low-E 366</li> <li>• Low-E 340</li> <li>• Low-E 180 Passive Solar</li> <li>• Low-E 366 w/i89</li> <li>• Low-E 180 w/i89</li> </ul> <p>• All insul glass above with Argon UNLESS specified or capillary tubes necessary for high altitudes.</p> <p><b>Glass Spacer Channel for Standard 3/4" Insul options:</b></p> <ul style="list-style-type: none"> <li>• Standard Intercept Spacer</li> <li>• Cardinal XL Edge Spacer</li> <li>• Dark Bronze XL Edge Spacer</li> </ul> <p>Please note that not all spacer options are available with all glass types.</p>	<p><b>Tints:</b></p> <ul style="list-style-type: none"> <li>• Bronze Tint</li> <li>• Grey Tint</li> <li>• Green</li> <li>• Custom, Specify</li> </ul> <p>• <b>Obscure Glass:</b></p> <ul style="list-style-type: none"> <li>• Obscure - Standard</li> </ul> <p><b>Tempered:</b></p> <ul style="list-style-type: none"> <li>• Both lites</li> <li>• 1 Lite, Exterior</li> <li>• 1 Lite, Interior</li> </ul> <p>• <b>With capillary tubes.</b> Specified for units that travel over high altitudes.</p>
<p><b>Hardware</b></p>	<ul style="list-style-type: none"> <li>• <b>Sweep Locks &amp; Keepers:</b> Positive locking mechanism surface mounted lock and keeper located on the meeting rail. Made of zinc die cast. <ul style="list-style-type: none"> <li>• 1 lock for basic unit frame widths of 22" (559mm) and less.</li> <li>• 2 locks for basic unit frame widths of 22" (559mm) and greater.</li> <li>• Standard finish is White.</li> </ul> </li> <li>• <b>Tilt Latches:</b> Spring loaded tilt latches surface mounted on the inside rail of sash. Made of vinyl, standard finish is white.</li> </ul>		
<p><b>Balance System</b></p>	<ul style="list-style-type: none"> <li>• <b>Inverted type Constant Force balance system.</b> Includes balance carrier with clutch shoe, balance coil(s), and balance clip and clip fasteners.</li> <li>• Sash are supported by 1, 2, or 3 coils, dependant on sash size and weight.</li> <li>• White or beige sash stop.</li> <li>• No adjustments necessary.</li> </ul>		
<p><b>Weatherstrip</b></p>	<ul style="list-style-type: none"> <li>• Operating units are provided with pile and bulb weatherstripping designed for a tight seal when sash are closed.</li> <li>• Weatherstripping system include: <b>On Sash:</b> <ul style="list-style-type: none"> <li>• 1 (One) Pile weatherstrip applied to top rail.</li> <li>• 1 (One) pile weatherstrips applied to each stile.</li> <li>• 2 (Two) pile weatherstrips applied to jambs.</li> <li>• Offset Bulb weatherstrip applied to bottom rail.</li> </ul> </li> <li>• <b>On Frame:</b> <ul style="list-style-type: none"> <li>• Pile weatherstrip at head &amp; sill.</li> </ul> </li> </ul> <p>No Weatherstrip on fixed picture/transom windows.</p>	<p><b>Color:</b> White.</p>	

	Standard Features	Standard Options	Customizing / Special / Optional
Insect Screen	<ul style="list-style-type: none"> <li>• Removable insect screens provided for operating sash, fitted to the exterior of the window unit.</li> <li>• Lift-In design with 2 spring plungers on the top rail of the screen and 2 lift tabs at the bottom rail.</li> <li>• Full screens only.</li> <li>• Screen fabric is 18 x 16 fiberglass mesh.</li> <li>• Screen frame is roll-form aluminum 0.030" (.762mm).</li> <li>• Screen frame color is white or beige. Exterior screen color matches exterior frame color.</li> <li>• Screen applied to unit when shipped.</li> </ul>		
Grille Options	<p><b>GIAS (Grille In Airspace)</b></p> <ul style="list-style-type: none"> <li>• Flat (profile), 5/8" x 3/16" (16mm x 5mm)</li> <li>• Contour (profile), 11/16" x 5/16" (18mm x 8mm)</li>   <li>• 7/8" (22mm) SDL (Simulated Divided Lite)</li> <li>• 2" (51mm) SDL (Simulated Divided Lite)</li>   <li>• Internal Spacer for SDL: <ul style="list-style-type: none"> <li>• With</li> <li>• Without</li> </ul> </li> <li>• Internal Spacer Color: <ul style="list-style-type: none"> <li>• Standard</li> <li>• Dark Bronze Anodized</li> <li>• Light Bronze Anodized</li> </ul> </li> </ul>	<p>Grille patterns:</p> <ul style="list-style-type: none"> <li>• Colonial</li> <li>• Queen Anne</li> <li>• Ladder</li> <li>• Craftsman</li> </ul> <p><b>Specify Exterior Grille Color:</b></p> <ul style="list-style-type: none"> <li>• Match Exterior Color (standard)</li> <li>• White</li> <li>• Beige</li> <li>• Colonial Red</li> <li>• Bronze</li> <li>• Linen</li> <li>• Hartford Green</li> <li>• Black</li> <li>• Gull Gray</li> </ul>	<p><b>Grille Pattern:</b> Special upon request.</p>
Options	<ul style="list-style-type: none"> <li>• NFRC rated.</li> <li>• Thermal values available on <a href="http://www.supersealwindows.com">www.supersealwindows.com</a>.</li> <li>• DP labels applied.</li> </ul>		
Additional Glass Specifications	<ul style="list-style-type: none"> <li>• <b>Low-E (standard):</b> dual insulated glass consisting of one lite of multi-layered 7138 Low-E coatings sputter coated on the #2 surface and one lite of clear glass. Argon filled.</li> <li>• <b>Clear:</b> dual insulated glass consisting of two lites of clear glass.</li> <li>• <b>Low-E 366:</b> dual insulated glass consisting of one lite of multi-layered 366 Low-E coatings sputter coated on the #2 surface and one lite of clear glass.</li> <li>• <b>Low-E 180 Passive Solar:</b> dual insulated glass consisting of one lite of multi-layered 180 Low-E coatings sputter coated on the #3 surface and one lite clear glass.</li> </ul>		
Warranty	<p>Warranty Period, Transferrable</p> <p>A. Glass Stress Cracks: 1 (one) Yr. Limited Warranty - Residential; 1 (one) Yr. Limited Warranty - Commercial.  B. Parts and Screens: 10 (ten) Yr. Limited Warranty.  C. Vinyl Mainframe: 20 (twenty) Yr. Limited Warranty - Residential; 10 (ten) Yr. Limited Warranty - Commercial.  D. Exterior paint: 10 (ten)-Yr. limited warranty.  E. Dual Insulated Glass: 20 (twenty)- Yr. limited warranty; Specialty Glass: 5 (five) Yr. Limited Warranty.  F. Warranty Labor: 2 (two) Yr. Limited Warranty.</p> <p>Please review the Sierra Pacific Windows Limited Warranty for Vinyl Products Effective May 1, 2017, for complete details and exclusions.</p>		
Manufacturer	<p>Sierra Pacific Windows; 1815 Water Street, Merrill, WI 54452. Toll Free Tel: 800-433-4873.  Web: <a href="http://www.supersealwindows.com">http://www.supersealwindows.com</a>.</p>		